DART SERVICE INSTRUCTION

TO AMEND INSTALLATION INSTRUCTIONS II130-4 REV. B AND EARLIER AND INSTRUCTIONS FOR CONTINUED AIRWORTHINESS ICA130-4 REV.0

> REF. TCCA STC: SH18-50 REF. FAA STC: SR04327NY REF. EASA STC: 10069009

1.0 PURPOSE:

It has come to DART's attention that the Liferaft Reservoir Assembly does not install properly with the Reservoir Brackets on the H130 Emergency Float System, P/N 652.2002, S/N VT093997.

The purpose of this service instruction is to provide parts and instructions to shift the Reservoir Brackets aft by 1.0 inch to allow for the Liferaft Reservoir Assembly to install properly. DSI 9831-011 Liferaft Reservoir Bracket Adjustment Kit will be used for the adjustment.

2.0 PROCEDURE:

- 2.1 Install each Reservoir Bracket Assembly, P/N 652.4701 onto an Adjustment Plate, P/N 654.0810 using quantity 2X MS24694C53 Screws, quantity 2X NAS1149C0332R Washers, and quantity 2X MS21043-3 Locknuts.
- 2.2 Remove Forward Floor Panel that has the Plate Doubler installed, from the Aft Baggage Compartment.
- 2.3 Install the modified Reservoir Brackets onto the Plate Doubler and Forward Floor Panel, within the Aft Baggage Compartment, in the location shown in II130-4, Figure 39, using quantity 4X AN3C10A
- 2.4 Fit check the Forward Floor Panel. Remove any excess material from the Adjustment Plate if needed. Spot Alodine 1201 any reworked sections per MIL-DTL-5541.
- 2.5 Match drill pilot holes, located on the Adjustment Plate, through the Plate Doubler and Forward Floor Panel using a #30 drill bit.
- 2.6 Install quantity 6X MS20470AD4-10 rivets into the previously drilled holes. Note: It is acceptable to upsize or downsize rivets to other MS20470AD4-X or equivalent rivet (customer supplied) to fit the installation.
- 2.7 Reinstall Forward Floor Panel, which now has the Plate Doubler and modified Reservoir Brackets installed
- 2.8 Install Reservoir Assembly in accordance with II130-4, starting at step 5.2.1.6.
- 2.9 Update aircraft logbook to indicate installation of DSI 9381-011 Liferaft Reservoir Bracket Adjustment Kit.

3.0 PARTS LIST


F/N	QTY -011	PART NUMBER	DESCRIPTION
	Х	DSI 9831-011	Liferaft Reservoir Bracket Adjustment Kit
1	2	652.4701	Reservoir Bracket Assembly
2	2	654.0810	Adjustment Plate
3	4	MS24694C53	Screw
4	4	NAS1149C0332R	Washer
5	4	MS21043-3	Locknut
6	6	MS20470AD4-10	Rivet
7	4	AN3C10A	Bolt
8	4	NAS1149C0363	Washer

CANADA DEPARTMENT OF TRANSPORT AIRCRAFT CERTIFICATION BRANCH DAO # 01-O-01

DATE: CERT. NO.: SH18-50 ISSUE NO .:

A	NEW IS	SUE	DM		19.07.12	
REV.			DESCRIPTION BY DA		DATE	
DESIGN		DM	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA			
DRAWN		DM				
CHECKED		MB	DRAWING NO.		REV. A	
MFG. A	PPR.	N/A	DSI 9831		SHEET 1 OF 2	
APPRO	VED	VS ,	TITLE		SCALE	
DE APPR.		DS	BRACKET ADJUSTME	NT	NTS	
DATE	19.0	7.12	COPYRIGHT © 2019 BY DART AEROSPACE LTD. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY DIRECTIONS OF COPIETO OR CAMBRILLY ATEST, ANY COVER DESCRIPTION OF THE COPIETO OR CAMBRILLY ATEST, ANY COVER DESCRIPTION OF THE COPIETO OR CAMBRILLY ATEST, ANY COVER DESCRIPTION OF THE COPIETO OR CAMBRILLY ATEST, ANY COVER DESCRIPTION OF THE COPIETO OR CAMBRILLY ATEST, ANY COVER DESCRIPTION OF THE COPIETO OR CAMBRILLY ATEST, ANY COVER DESCRIPTION OF THE COPIETO OR CAMBRILLY ATEST.			

NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.



4.0 WEIGHT AND BALANCE:

This DSI has negligible effect on Weight and Balance.

DESIGN	DM	DART AEROSPACE LI	D	
DRAWN	DM	HAWKESBURY, ONTARIO, CANADA		
CHECKED	MB	DRAWING NO.	REV. A	
MFG. APPR.	N/A	DSI 9831	SHEET 2 OF 2	
APPROVED	VS 📶	TITLE	SCALE	
DE APPR.	DS	BRACKET ADJUSTMENT	NTS	
DATE 19.0	7.12	COPYRIGHT © 2019 BY DART AEROSPACE LTD. THIS DOCUMENT IS PRIVATE AND COMPIDENTAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.		